



HIND MOULD RELEASE OB

PRODUCT DATA SHEET

MINERAL OIL BASED SHUTTER RELEASE AGENT

DESCRIPTION

Hind Mould Release OB Low viscous mineral oil based shutter release agent. Ready for direct application and use.

USES

HIND Mould Release OB can be used:

- To Provide quick, clean and easy stripping of Concrete moulds, Mivan shuttering and Aluminum form work.
- To obtain clean and smooth concrete surface.
- To protect steel and wooden form work.

ADVANTAGES

- Minimum cleaning of shutters before re-use.
- Extended life of form work.
- Can be used on all types of form work.
- Improved finish, stain and air free fair faced concrete.
- High coverage.
- Non corrosive to steel.
- Dust free concrete surface.

APPLICATION

Apply one coat only by brush, roller or spray on the clean surface. **Hind Mould Release OB** after application should be allowed to dry before concreting takes place.

PROPERTIES

Aspect	Light brownish/ Light greenish liquid
Coverage	20 to 50 Sq. mtr. /Litre
	The consumption depends on the surface texture and porosity of
	the form work.

SHELF LIFE

12 months from the date of manufacture. Container should be protected from sunlight and naked flame.

PACKING

105, 210 Ltr. Container

HANDLING PRECAUTION

Hind Mould Release OB is non-toxic but ingestion is to be avoided. Any splashes to the skin must be washed with water. If contact with eyes occurs, wash well immediately with water and seek medical advice.

Note:

- Hindcon Chemicals maintains a team of technically trained professionals to provide full support to your problems in construction, and recommend the correct product to
 suite your specific requirements. Our authorized applicators can attend your site for application of the products.
- The content of the Technical datasheet are for general information and guideline. The result shown here are generated from our laboratory or from our site experiences.
 Quality of our products are maintained as per ISO9001:2008 recommendations and continuous researches. The behavior can change as per the prevailing conditions at the
- Quality of our products are maintained as per ISO90012008 recommendations and continuous researches. The behavior can change as per the prevaling conditions at the time of applications.
 Since HINDCON CHEMICALS LIMITED has no control over the use to which the users may put the material, it does not claim or warrant that in the user's particular
- Since HINDCON CHEMICALS LIMITED has no control over the use to which the users may put the material, it does not claim or warrant that in the user's particular
 circumstances, the result that the user will obtain from the product will be the same as those described in this communication or that the user will find the information or
 recommendations complete, accurate or useful. The client must test and ascertain the safety and fitness for the product for use.

HINDCON CHEMICALS LIMITED (Formerly HIND SILICATES PVT. LTD) (AN ISO 9001: 2008 COMPANY)

Office:

62B, Braunfeld Row, "VASUDHA", Kolkata - 700027 Tel: 24490835, 24490839. Fax: 24490849 E-mail: <u>contactus@hindcon.com</u>, hindconchemicals@yahoo.com Factory: Baniyara, Jalan Complex, Gate No.3 Howrah – 711 411. Tel: 2669 9213 www.hindcon.com