



## HIND SEALANT PRIMER

### PRODUCT DATA SHEET

#### PRIMER FOR POLYSULPHIDE SEALANTS

#### DESCRIPTION

**Hind Sealant Primer** is a low viscosity primer which is very essential to be applied on the surface for proper bonding before the application of Polysulphide Sealant.

#### USES

**Hind Sealant Primer** is used in conjunction with **Hind Sealant PS**. It is recommended for the surface namely concrete, brickwork, asbestos, cement, gypsum, board, stone, glass, timber, rigid PVC, anodized aluminum, ceramics etc. Primer is not required for Epoxy and Polyester surfaces.

#### ADVANTAGES

- Easy to apply
- Fast recoat time
- Better bonding

#### APPLICATION

Prime only on two sides of the property prepared joint surface with **Hind Sealant Primer** by brush and allow it to cure for minimum 20 minutes. Apply two coats of **Hind Sealant Primer** at an interval of 30 minutes. After priming is over **Hind Sealant PS** should be filled in the joints.

#### COVERAGE

For porous and nonporous surface coverage of **50 – 55 ft<sup>2</sup> / Ltr /coat** is achieved.

#### SHELF LIFE

12 months from the date of manufacture in unopened condition. Keep in cool and dry place.

#### PACKING

200 / 250 ml. in containers

#### HANDLING PRECAUTIONS

**Hind Sealant Primer** is non-toxic and ingestion to be avoided. Any splashes to the skin must be washed with water. If contact with eyes occurs, wash well immediately with water and seek medical advice.

#### Note:

- Hindcon Chemicals maintains a team of technically trained professionals to provide full support to your problems in construction, and recommend the correct product to suite your specific requirements. Our authorized applicators can attend your site for application of the products.
- The content of the Technical datasheet are for general information and guideline. The results shown here are generated from our laboratory or from our site experiences.
- Qualities of our products are maintained as per ISO9001:2008 recommendations and continuous researches. The behavior can change as per the prevailing conditions at the time of applications.
- Since **HINDCON CHEMICALS LIMITED** has no control over the use to which the users may put the material, it does not claim or warrant that in the user's particular circumstances, the result that the user will obtain from the product will be the same as those described in this communication or that the user will find the information or recommendations complete, accurate or useful. The client must test and ascertain the safety and fitness for the product for use.

#### HINDCON CHEMICALS LIMITED

(Formerly HIND SILICATES PVT. LTD)  
(AN ISO 9001: 2008 COMPANY)

#### Office

62B, Braunfeld Row, "VASUDHA", Kolkata - 700027  
Tel: 24490835, 24490839. Fax: 24490849

E-mail: [contactus@hindcon.com](mailto:contactus@hindcon.com), [hindconchemicals@yahoo.com](mailto:hindconchemicals@yahoo.com)

#### Factory

Baniyara, Jalan Complex, Gate No.3  
Howrah – 711 411. Tel: 2669 9213

[www.hindcon.com](http://www.hindcon.com)