



HIND TILE GROUT

PRODUCT DATA SHEET

READY TO USE TILE JOINT FILLER

DESCRIPTION

Hind Tile Grout is an ideal cementitious based, ready to use, gap filling material for wall and floor tiles like vitrified, ceramic, mosaic, marble and glazed tiles etc.

USES

Hind Tile Grout is used to filling up the wall and floor joints when tiles like vitrified, ceramic, mosaic, marble and glazed tiles etc. are fixed in residential and industrial buildings.

ADVANTAGES

- Ready to use, only **Water/ Polymer (50% Polymer, 50% Water for better result)** is to be added.
- It ensures excellent bond with different types of tiles.
- Makes the joints waterproof.
- Dust penetration resistant.
- Is unaffected and can withstand effects of mild detergents and cleaning agents.
- Cleaning becomes easy.

APPLICATION

Surface Preparation

All substrate must be structurally sound, clean and free from any contamination like grease, oil, loose particles etc. before application of **Hind Tile Grout**.

Mixing

Add 340-360 gms. **Water/ Hind Crete Plus WPM (Acrylic Polymer, for better result)** to 1 Kg of **Hind Tile Grout** by volume and mixing is to be done properly by a trowel to get a paste type consistency. Allow the Tile grout paste to settle for 10-12 minutes in the mixing pan. The paste is then applied to fill the joints by means of spatula, trowel and finally it is smoothed evenly to level and finish. Surplus grout paste is removed by a damp sponge. Care should be taken while cleaning the surplus grout from getting it pressed down before drying. The tile grout is allowed to dry for hours after application. We must always ensure that tile grout should be filled into the joints, 24 hours after the tile fixing operation is completed.

PROPERTIES

Aspect	Powder
Color	Ivory, white, black, grey, copper brown, cream, blue, green, brick red, sky blue and yellow.
Bulk Density	0.95 Kg/Ltr. at 27 ⁰ C.
Coverage	1 Kg covers approx. 95-100 Sq.ft (ceramic tiles) and 75-80 Sq.ft (vitrified) for joint size of 3mm width.
Working Time	Approx. 30-45 minutes at 27 ⁰ C.

PACKING

Available in 1 Kg Pack

SHELF LIFE

6 months from the date of manufacture, provided the material is stored in a perfectly dry place and in unopened conditions.

HANDLING PRECAUTION

Hind Tile Grout is non-toxic and inhalation of the powder material is to be avoided. If contact with eyes occurs was with plenty of water.

Note:

- Hindcon Chemicals maintains a team of technically trained professionals to provide full support to your problems in construction, and recommend the correct product to suite your specific requirements. Our authorized applicators can attend your site for application of the products.
 - The content of the Technical datasheet are for general information and guideline. The result shown here are generated from our laboratory or from our site experiences.
 - Qualities of our products are maintained as per ISO9001:2008 recommendations and continuous researches. The behavior can change as per the prevailing conditions at the time of applications.
 - Since **HINDCON CHEMICALS LIMITED** has no control over the use to which the users may put the material, it does not claim or warrant that in the user's particular circumstances, the result that the user will obtain from the product will be the same as those described in this communication or that the user will find the information or recommendations complete, accurate or useful. The client must test and ascertain the safety and fitness for the product for use.
-

HINDCON CHEMICALS LIMITED
(Formerly HIND SILICATES PVT. LTD)
(AN ISO 9001: 2008 COMPANY)

Office
62B, Braunfeld Row, "VASUDHA", Kolkata - 700027
Tel: 24490835, 24490839. Fax: 24490849
E-mail: contactus@hindcon.com, hindconchemicals@yahoo.com

Factory
Baniyara, Jalan Complex, Gate No.3
Howrah – 711 411. Tel: 2669 9213
www.hindcon.com